

**Seismic Calculator**

**User Manual**

**IPLAB**

**Copyright © 2016 IPLAB. All rights reserved.**

This work contains the confidential and proprietary trade secrets of IPLAB and may not be copied or stored in an information retrieval system, transferred, used, distributed, translated or retransmitted in any form or by any means, electronic or mechanical, in whole or in part, without the express written permission of the copyright owner.

**Start:**

**Seismic attributes->**

**Seismic Calculator**

**The seismic calculator use the following rules:**

- 1. The defined procedure used to calculate every sample in result cube.**
- 2. There are several predefined variables.**
  - **I, J, K – index for current sample**
  - **X, Y, Z – coordinates for current sample.**
  - **nI, nJ, nK – size of the moving window with available neighboring samples for calculation around current samples.**
  - **Cube – array with values in moving window. Size of the array is Cube[ncube][nI,nJ,nK] where ncube -is number cubes used like input.**
  - **Seis0, Seis1, ..., Seis'ncube' – predefined values of the cubes used like input for current sample (center of the moving window).**
- 3. Result cube of the procedure can be only one for one run.**
- 4. Result cube will be virtual.**
- 5. Name of the result cube will be defined by variable with '=' (TokenKind.ASSIGN). For example if we have procedure string:**  
*cubeResult=100;*  
**it create new virtual cube with name "cubeResult" with constant value=100.**
- 6. If we use several strings for procedure, only last ASSING will define procedure result. For example if we have procedure string:**  
*d=(X-1000)\*(x-1000)+(y-3000)\*(y-3000)*  
*cubeResult=sqrt(d);*  
**it create only one new virtual cube with name "cubeResult"**
- 7. Procedure can use several predefined function sin(), cos(), abs(), pow(), atan2(), sqrt(), exp(), log(), sign(), rand(), iif(,,).**
- 8. Additionally all function like Math.Sqrt(), ... can be used.**
- 9. C# constrictions like for(;;) {}, if() else, and any other can used.**

**10. Below example to calculate simple coherence attribute:**

```
double sum=0;
int n=0;
for(int k=0; k< nK; k++)
{
    for(int i=0; i< nI; i++)
        for(int j=0; j< nJ; j++)
        {
            int ii =nI/2+1;
            int jj =nJ/2+1;
            var diff=abs(Cube[0][i,j,k]- Cube[0][ii,jj,k]);
            var norm=abs(Cube[0][i,j,k]+ Cube[0][ii,jj,k]);
            if(norm==0)norm=1000000; // protect to division to zero
            var rez= (diff/norm);
            sum+=rez;
            n++;
        }
}
coherence=sum/n;
```




Figure 1: Seismic calculator